

SOASTA 54.15 (CloudTest/TouchTest 7732.194)

Mar 26, 2015

Table of Contents

SOASTA 54.15 (CloudTest/TouchTest 7732.194)	1
Bugs Fixed	1
CloudTest	1
TouchTest	2
SOASTA 54.14 (CloudTest/TouchTest 7732.189)	3
Bugs Fixed	3
TouchTest	3
SOASTA 54.13 (CloudTest/TouchTest 7732.186)	4
Enhancements	4
CloudTest	4
Cloud Provider Account icons for Global Arcs (90967)	4
Bugs Fixed	5
CloudTest	5
TouchTest	5
SOASTA 54.12 (CloudTest/TouchTest 7732.159)	6
Bugs Fixed	6
CloudTest	6
TouchTest	7
SOASTA 54.11 (CloudTest/TouchTest 7732.141)	8
Bugs Fixed	8
CloudTest	8
TouchTest	9
SOASTA 54.10 (CloudTest/TouchTest 7732.127)	10

Enhancements	10
TouchTest	10
Bugs Fixed	11
CloudTest	11
TouchTest	12
SOASTA 54.09 (CloudTest/TouchTest 7732.123)	13
Bugs Fixed	13
CloudTest	13
SOASTA 54.08 (CloudTest/TouchTest 7732.119)	14
Bugs Fixed	14
CloudTest	14
SOASTA 54.07 (CloudTest/TouchTest 7732.107)	15
Bugs Fixed	15
CloudTest	15
TouchTest	15
SOASTA 54.06 (CloudTest/TouchTest 7732.102)	16
Bugs Fixed	16
CloudTest	16
TouchTest	17
SOASTA 54.05 (CloudTest/TouchTest 7732.84)	18
Bugs Fixed	18
CloudTest	18
TouchTest	19
SOASTA 54.04 (CloudTest/TouchTest 7732.71)	21
Bugs Fixed	21
CloudTest	21
SOASTA 54.03 (CloudTest/TouchTest 7732.62)	22

Features	22
CloudTest	22
Global Activity	22
Globe System Dashboard.....	23
Dynamic Globe Dashboard.....	23
Activity Arc Controls	25
Labels and Markers	25
Flyout Labels	25
Pinpoint Markers	26
Arc Color (Error Rate).....	27
Arc Control sliders.....	28
Pulse Controls	29
Pulse Color (Average Message Response)	29
Pulse Control sliders	29
Other CloudTest Globe Settings.....	30
Favorite Locations.....	30
Globe Style	31
General Settings	32
CloudTest Activity Legend	33
Globe Filtering.....	33
Cloud Provider Account Support for QingCloud.....	34
Setup QingCloud as a Cloud Provider	34
QingCloud Server Instance Types.....	36
Launching Test Servers using QingCloud	37
Creating a Grid using QingCloud	37
Custom Commands for Monitoring	41
Creating a Custom Command Monitor	42

Enhancements	46
CloudTest.....	46
Support for Transport Layer Security (TLS) 1.1 and 1.2	46
Support for Server Name Indication (SNI)	46
Java Custom Module Improvements	46
Metric Labeling in Monitors	47
Updating CloudTest Lite (Non-Automated Build Upgrades)	48
Download and Install the SOASTA 54 version of CloudTest Lite	49
Upgrade to CloudTest Lite 54 on Mac OS X.....	49
Upgrade to CloudTest Lite 54 on Windows	50
Support for Additional HTTP Methods (78361)	52
Support for Monitoring JBoss 8 (30032)	54
Ability to put any percentile into Collection Analysis (Hierarchical) widget (84993)	54
TouchTest	55
Test Suite Dashboard Improvements	55
Errors Only Display in Compositions Overview Widget	55
Additional Component Selection Support in Compositions Overview Widget	56
Import/Export of Test Suite Results	57
New <code>includechildresults</code> parameter for <code>sCommand</code>	57
Launch Composition Details in <code>sCommand</code> JUnit/XML (88321)	58
New <code>MakeAppTouchable</code> (MATT) Command Line Syntax	59
Bugs Fixed	60
CloudTest.....	60
TouchTest	64

SOASTA 54.15 (CloudTest/TouchTest 7732.194)

Bugs Fixed

CloudTest

91362: HP Cloud leaves behind ports on deployment error and HP deployment improvements

This fix changes the search for servers after they are started, now instead of using unpredictable changes-since, search is done by name, which use a SOASTA-generated UUID. Additionally, this fix includes code for if an HP server launches into Error status, we clean up its resources, and launch a new one.

90110: WebSocket recording does not capture single-character receives

This issue happened because of incorrectly reading the mask of the WebSocket frame.

91092: Conductor using Websocket option does not record anything

The Conductor recorded fine without the WebProxy option enabled, however, after enablement nothing gets recorded (HTTP or WS).

87268: Increase CLOUDTEST_JBOSS_HEAP_SIZE for r3.4xlarge Main in a dual-instance environment

The heap size has been adjusted accordingly.

TouchTest

91046: Android app crashed after few steps while recording [[requires new TouchTestDriver](#)]

The given Android app was not recordable using the prior TouchTest Driver.

SOASTA 54.14 (CloudTest/TouchTest 7732.189)

Bugs Fixed

TouchTest

91509: TouchTest Lite signup page didn't handle exceptions caused by expired links

TouchTest Lite users who accessed links that had expired sessions received errors rather than the expected Login screen.

SOASTA 54.13 (CloudTest/TouchTest 7732.186)

Enhancements

CloudTest

Cloud Provider Account icons for Global Arcs (90967)

Cloud Provider Account (CPA) icons now appear with Arc labels as of this release.



Arcs will display the corresponding CPA icon to provide additional visual input in test compositions utilizing any supported Cloud Provider account.

Bugs Fixed

CloudTest

84416: Some Azure Cloud Services are not deleted when servers get deleted

This could happen if the cloud service was created but deploying a VM in this cloud service somehow fails. Previously, we only deleted cloud services that contained running VMs. Now, we will instead keep a list of cloud services that were created as a part of grid deployment.

71075: Backup and Restore not working

Backup was not including sequence tables for large databases so the restore would not work.

TouchTest

90691: iOS TT: Specific items on page always return item is not accessible or enabled when it should be accessible [\[requires new TouchTestDriver\]](#)

For UILabel in UICollectionView, make the claim that they're accessible.

85460: Touch Locator Tool not working on 64-bit devices for apps compiled with arm64 [\[requires new TouchTest Web app\]](#) | [\[requires new TouchTestDriver\]](#)

Using the Touch Locator tool to identify objects on the device screen (iPhone 5s/iOS8.2) unexpectedly failed (e.g. selection does not grey-out, and touching the screen results in empty Locator boxes). This release includes fixes to WEPopover library files that resolve the issue.

SOASTA 54.12 (CloudTest/TouchTest 7732.159)

Bugs Fixed

CloudTest

90427: Remove "Stop JBoss" button from CloudTest Admin

As of this release, the CloudTest Admin no longer permits the user to stop the underlying JBoss server.

89676: Find and Replace hangs when executing on a recording that contains WebSocket messages

Attempting Find and Replace would hang the system if a recording was searched that also had WebSocket messages.

69410: Allow Concurrent Logins for Non-browser Sessions (except Lite products)

In prior releases, API and 3rd party sessions would evict concurrent browser sessions. Now, Concurrent logins are permitted in all SOASTA versions with the exception of Lite product versions.

42931: Transfer-Encoding should take the place of a Content-Length header

CloudTest failed to correctly recognize that Transfer-Encoding should take the place of a Content-Length header in a Packet recording, which resulted in this Java HTTP exception when CloudTest attempted to send both header types.

TouchTest

90713: Android TT: Locators returned during clip recording are only generic Xpath or classname[#] [\[requires new TouchTestDriver\]](#)

This fix allows recording of IDs in obfuscated apps by using the Android activity API.

SOASTA 54.11 (CloudTest/TouchTest 7732.141)

Bugs Fixed

CloudTest

90712: Error thrown when Set-Cookie domain is blank

CT throws an error (albeit a very descriptive error) when the domain attribute of the Set-Cookie response header is blank. Now, the host is used for the cookie domain, if necessary.

90552: Conductor | Zaproxy fails to load on Windows 7 on VMWare Fusion seamless mode

While using Zaproxy on Windows VM using VMWare fusion, zaproxy failed to start since it uses a default home directory that is read only. A Windows-specific fix for setting the home directory has been added.

90477: Missing string for Environment lower panel

The Region label was missing in the Environment lower panel, General tab.

90210: TouchTest Clip Editor: Unable to put Clip into Group when only item in Clip

The Create a Group context command was missing if an embedded clip was placed into an empty clip and then selected.

TouchTest

87100: App can record but crash on playback [[requires new TouchTestDriver](#)]

This fixes instrumentation when the `inputManager` method invocation fails

71379: Android: this should report the exception in the result and bring back TouchTest Agent [[requires new TouchTestDriver](#)]

This fix improves the crash handler mechanism for Android.

SOASTA 54.10 (CloudTest/TouchTest 7732.127)


Enhancements

TouchTest

88142: Target Editor Now Includes Authentication Fields for Mobile Web Targets (WebUI/iOS)

The WebUI/Ajax Target Editor now includes additional certification fields for web mobile targets akin to those provided for HTTP targets.

To utilize these authentication fields, please create a WebUI/Ajax target, and in the Target Editor change its browser type to TouchTest Web, after which the User Name and Password fields shown below will appear.



The screenshot displays the Target Editor interface, divided into two main sections: Settings and Authentication. In the Settings section, the Browser dropdown is set to 'TouchTest Web', with a blue tooltip that reads 'Choose this browser type to test a web application on an iOS device.' The Conductor dropdown is set to 'Any Suitable Conductor' and the Device Agent dropdown is set to 'Any Device Agent'. There is an unchecked checkbox labeled 'Enable HUD'. The Authentication section contains two input fields: 'User Name' and 'Password'.

Bugs Fixed

CloudTest

**90438: Deleting a User via sCommand causes an error Exception:
java.lang.NullPointerException**

The sCommand Utility failed with this null pointer, likely was because temporary tokens, created in `Service.getTemporaryUserToken()`, did not have usernames.

83499: SSL error when hitting Cloud-based Java 1.7 API with client certificate

This fix disables Server Name Indication (SNI) for hosts that are known to not support it.

TouchTest

90309: Android: Error "Unknown=null" locator displays in Playback if MATT (53.20) was used [[requires new TouchTestDriver](#)]

Locators with upper case letters would incorrectly return an unknown locator.

88182: Android TTW: Double click does not execute on Android tablets running OS 4.4.2 [[requires new TouchTest Web app](#)] | [[requires new TouchTestDriver](#)]

An issue with double click duration was encountered.

SOASTA 54.09 (CloudTest/TouchTest 7732.123)

Bugs Fixed

CloudTest

90372: eu-west-1 missing from EC2 install

The Amazon EC2 region, eu-west-1, was unexpectedly unavailable in the install image for 54.08. This error was limited to the 54.08 release.

89607: sCommand IndexOutOfBoundsException

In prior sCommand versions, the underlying code erroneously presumed that at least one result would be generated with each Play command. When a scenario arose where no such result per Play was in existence at runtime, this error would occur. Now, whatever result information exists at runtime (e.g. former behavior) from the instance's status object will be used if no result exists.

88610: VPC Bug for Server List

A given VPC environment was not launching and under further investigation proved to have been installed with a broken Server List. This fix resolves the underlying issue.

SOASTA 54.08 (CloudTest/TouchTest 7732.119)

Bugs Fixed

CloudTest

90348: A label on parallel repeats settings is wrong in Composition Editor

The Composition Editor, lower panel Repeat tab, Repeat Method label was incorrectly labeled as the Renew Parallel Repeats field.

90315: java.lang.NullPointerException

This null pointer exception happened in SOASTA Central.

90294: AppDynamics Error

An error occurred while adding a widget from this external data source.

90239: WebSocket Recording causes site HTTP 400 error

Authentication steps while recording the target site would cause this error.

SOASTA 54.07 (CloudTest/TouchTest 7732.107)

Bugs Fixed

CloudTest

90239: Recording causes the site to give HTTP 400 error

A WebSocket URL would produce this HTTP 400 error while recording, although if recording wasn't active no such error was produced. This fix modifies the WebSocket proxy only.

TouchTest

88182: Android TTW: Double click does not execute on Android tablets running OS 4.4.2 [[requires new TouchTest Web app](#)]

This fix augments the earlier reported fix by reducing the interval between multiple taps in a single action to account for slower devices and VMs.

SOASTA 54.06 (CloudTest/TouchTest 7732.102)

Bugs Fixed

CloudTest

90084: The time aggregate for WebSocket Open calls didn't include TTFB, TTLB, and Bytes Received

Time aggregates such as TTFB, TTLB, and so forth, were unexpectedly omitted.

89759: Import dialog cannot store FileItem objects in the HTTP session

An object stored in the HTTP session was persisted to the Repository where it could not later be de-serialized. This fixes the error "the null attribute Type is not recognized."

89514: WebSocket Test not displaying response times or receive bytes

Response times in a WebSocket test weren't showing for for open and message sends and bytes received was blank.

88425: Maestro runs out of memory due to excess ResultEvent objects

A Java process that returned random errors would run to 100% while using CloudTest appliance.

85683: "Target Property Sets - Leading and Trailing text that was previously saved is not displayed when target is reopened"

Captured Leading Text and Trailing Text was unexpectedly omitted when the saved target was reopened.

84915: scommand java.lang.ArrayIndexOutOfBoundsException when using AverageResponseTime validation for empty Transaction

sCommand failed with an 'scommand java.lang.ArrayIndexOutOfBoundsException when using AverageResponseTime validation for Transaction with 0.00 avg' error when the validation= was in use if the transaction in question was empty.

TouchTest

89788: Can't scroll ListView in app [[requires new TouchTestDriver](#)]

MATT failed to instrument some classes in a package due to underlying failures in instrumenting some Google Play Services classes. This fix includes support for additional Google Play Services libraries.

88182: Android TouchTest Web: Double click does not execute on Android tablets running OS 4.4.2 [[requires new TouchTest Web app](#)]

Double click web actions unexpectedly failed on playback in Android. Now, for doubleClick (or any click w/ multiple tapCounts), TTW will reset by keeping track of scale tracker.

88606: Device Mismatch error

In a prior limited release, logging was added to better debug a device mismatch issue. Now, in addition, there is a new exception to give more details to the user on why their device was not verified. Future issues resulting from request manipulation of the type in question will now have warnings to point debuggers in the right direction.

SOASTA 54.05 (CloudTest/TouchTest 7732.84)

Bugs Fixed

CloudTest

89758: Custom Properties in Clip Editor is not shown for JA language

The Clip Editor, Custom Properties tab didn't show any content if Japanese was the language.

89757: Dependencies Tab is not showing for JA lang in Central

The Central, Dependencies tab failed to show any information if Japanese was the language.

88597: Recording Causes the site login process to timeout

This fix adds a new hidden "enabledSSLVersions" setting that can be used to enable only TLS 1.2. This fix requires that the user manually add a line to the Conductor config file using the following steps:

1. Stop the Conductor.
2. Edit ~/Library/Preferences/SOASTA/Conductor.cfg.xml.
3. Add the following line:

```
<param name="enabledSSLVersions" value="TLSv1.2" />
```

4. Save, start Conductor again, do the recording!

89514: WebSocket Test not displaying response times or receive bytes

While running WebCocket tests he response times didn't show for for the open and message sends. Also, the bytes received showed blank.

88304: QingCloud integration does not verify security groups

Before deploying a QingCloud grid, CloudTest will now automatically verify that ports 80 and 443 are open in the specified security group.

88266: Starting a monitor with Custom Command should fail if not using Conductor

The Custom Command for Monitoring feature unexpectedly permitted a monitor to be started on SSH, whereas a Conductor configured as a monitoring agent is required.

87882: Session Template Wizard has wrong page label allocation

The Session Template Wizard pages and navigation nodes had non-matching labels.

57674: Import of Composition failed with Null Pointer in CTLite

This was caused by some imprecise Xpath, which was picking up the "Distribution" node of a seed data user property, which has no places. The selector was changed to only apply to track distributions.

TouchTest

89539: iOS TT: After MATting application it crashes on opening splash screen [\[requires new TouchTestDriver\]](#)

This fix adds signing to embedded frameworks dylib to prevent crashing with add-on swift libraries.

67522: Error creating a device cloud if the name is already taken

This error would result if a Device Cloud was given an already existing name.

SOASTA 54.04 (CloudTest/TouchTest 7732.71)

Bugs Fixed

CloudTest

Azure (IaaS) grids did not deploy in 54.03

Grids for Azure (IaaS) were not deployable while running SOASTA 54.03 builds.

86136: Can't tear down/delete non-cloud RSDBs

Local Results Service databases could neither be torn down nor deleted.


SOASTA 54.03 (CloudTest/TouchTest 7732.62)

Features

CloudTest

Global Activity

With the advent of the Globe Dashboard in this release, SOASTA is also introducing Activity Arcs; an exciting new, geo-spatial depiction of real load tests, in real time. Activity Arcs depict the flow of server data from different data centers against the target site(s).




An Activity Arc depicts real-time data flow combining color (for error rate), width (for bandwidth), as well as other arc attributes including animation, gradient length, speed, height, and shape, in order to provide powerful visual reinforcement of the data flow in the test composition and in its result.

Two new System Dashboards—Globe Dashboard and the Dynamic Globe, display Activity Arcs. The Globe can also be added to new custom dashboards. Large screen displays are recommended and are the preferred vehicle for display of all SOASTA Globe Dashboards.

Globe System Dashboard

The Globe Dashboard presents the test composition's data stream in one dramatic, three-dimensional, WebGL-based global format with fly-to animation, and other Globe features readily available by drop-down settings.

The Globe System Dashboard presents the CloudTest Globe in a wide layout where it can be combined with other widgets while also functioning as a background.




CloudTest users should note that the Globe's Settings are found in the upper right drop-down panels rather than in the Dashboard Editor lower panel.

Arc animation is enabled by default and can be disabled in the Globe's Activity Arc panel (covered in the following section).

Use the [Widget-on-Widget Layout and Edge Constraints](#) procedure to add Charts to your own custom Globe Dashboard.

Set your custom Dashboard Theme to Dark to improve the blending between your widget-on-widget layout and the Globe's Starfield.




Dynamic Globe Dashboard

er names may be trademarks of their respective owners.

The Dynamic Globe System Dashboard combines the Globe and Dynamic Ramp Controller into an exciting new, geo-spatial depiction of real load tests, in real time.

In the Dynamic Globe Dashboard, an Activity Arc depicts the flow of data from the different data centers (e.g. cloud vendors) where load servers run against the target site. Once play is clicked in cloud-based load tests, or while reviewing results, the Globe shows an arc from any cloud-based data centers in use in the test.




Note: In general, the Globe is designed for large displays. In the context of the new Dynamic Globe System Dashboard this is especially true. The user experience may suffer notably on smaller displays such as laptop screens since the Dynamic Ramp Controller will overlap the Globe background.

Using the Globe as its background this new System Dashboard also presents the Average Response Time and Send Rate widgets. The Dynamic Ramp Controller in use in this System Dashboard has its top charts suppressed (e.g. via the widget's lower panel settings).

Activity Arc Controls


For CloudTest, a new Activity Arcs panel appears that was not found in the prior mPulse-only version of the Globe widget. Clicking the Arc icon on the Globe toolbar drops down the panel.



The Activity Arcs panel is divided into two main control tabs for Arc and Pulse—the Arc Controls panel displays by default. Additional settings for labels and markers appear at the top of the panel.


Labels and Markers

The Global Activity dashboard displays labels and markers that clearly identify data centers and target sites where the data flow begins and ends.




Flyout Labels

A Flyout Label is a two-line label that allows for a pair of text data fields (above and below).



Pinpoint Markers

A Pinpoint Marker is a 3D marker shown as a billboard (e.g. facing camera) that represents an origin or terminal point of the relevant portion of the data flow (e.g. the geo location of a Data Center or other data point).




When displayed on the currently visible portion of the Globe, markers and labels appear on the Globe surface (e.g. similarly to how they display while in 2D Mercator view).




As the Globe rotates, the markers and labels are presented as if floating in space.

Arc Color (Error Rate)

The error basis for Arc Color can be changed from Error Rate to



The default Arc Color settings can be modified in custom dashboards by adjusting the maximum value of the error ranges shown below.



Arc Animation is a subtle pulse effect on the arc layer (solid component) that is noticeable when the pulses layer is off. The **Enable Arc Animation** box is checked by default. Disable if you do not wish to see arc animation at all.

Arc Control sliders

Use the following Arc Control sliders to customize your arcs:

Arc Visibility – Use this slider to control the arc's opacity

Arc Width (Bandwidth) – Use this slider to control the arc's width with respect to bandwidth in the test composition

Arc Gradient Length – Use this slider to adjust the arc's "squircle" length



Arc Speed – Use this slider to control the arc's growth on creation and following subtle pulses along its length.

Arc Height – Use this slider to control arc height (e.g. the height in relation to the 3D globe or 2D map view)

Arc Shape – Use this slider to control arc shape (e.g. odd or even)


Pulse Controls

Click the Pulse Controls panel for additional settings. Pulse controls allow the user to experiment with different pulse frequencies, offsets, speeds (based on message rate), random variance and length. Pulses account for a great deal of the effects along the arc line, from a pure linear effect, to smaller pulses.



Pulse Color (Average Message Response)

The default pulse color settings shown below can be modified (just as in other Globe settings).



Pulse Control sliders

Pulse Control sliders are factor sliders, which is to say that they pertain to the message rate attached to pulse speed. The relative speed differences are scaled.

Use the following Pulse Control sliders to customize your arcs:

Pulse Visibility – Use this slider to control the pulse's opacity

Pulse Width (Bandwidth) – Use this slider to control the pulse's width

Pulse Length – Use this slider to control the pulse's "squircle" length. The slider is a factor

the relative speed differences are just scaled.

Pulse Speed – Use this slider to control the pulse's speed.

Pulse Frequency – Use this slider to control how frequently the pulse occurs.


The **Enable Pulse Animation** box is checked by default. Disable if you do not wish to see arc animation.

Other CloudTest Globe Settings

In addition to the **Activity Arcs** panel (covered in the **Dynamic Globe Dashboard** section below), CloudTest shares additional settings with the Globe Dashboard found in mPulse. The Globe toolbar panels are (from left to right) Favorite Locations, Activity Arcs, Globe Style, and General Settings.

Favorite Locations

Click the Star icon to access location settings in the Location drop-down.



- Click any listed location to fly-to its given location on the Globe.
- To add a new location, enter it into the entry field and click the Add.
- Click any default or custom location to fly to (out if you're already zoomed into a location, in if you're at satellite view) to the desired location. The default locations are Mountain View, CA; New York, NY; London, UK; Paris, France; Sydney, Australia; Singapore, and Hong Kong.
- Enter an integer in seconds to control the fly-to sequence's cycle speed.
- Click Home View to return to the location set as "Home View" (while in Edit mode use "Set as Home View" to make the current globe view home)

- To tour all of the locations, click the new Tour Locations command in the Locations drop-down. When you do so, the locations will load. Click the command a second time to begin the tour.

To rotate the globe at a steady rate, click Rotate. The globe background rotates along with the globe itself for increased realism.

Globe Style

Globe Style settings are found in the Globe dropdown. Choose from among the Base Imagery **globes** shown in the **Globe Style** drop-down.



Popular choices include:


- **Blue Marble** (the classic global nickname for our planet displays Earth as if from a satellite or a traveling spacecraft)
- **Street** (Shows the **globe** with political boundaries and

other features including street plotting

- **Aerial** (An aerial perspective **globe**)
- **Mono Dark** (mPulse Dark shows darkened land masses)
- **Mono Light** (mPulse Light shows white land masses)
- Other available views include Satellite, Hybrid, (alternate) Street, Terrain, Storm, and Mongo Terrain

General Settings

General Settings are found under the Gear icon.



Display Legend — Check/uncheck the Display Legend to toggle the legend on the Globe surface

Alignment — Set widget alignment to left, right, or center by selecting a radio button.

Rotation Speed — Use the rotation speed to control the rate at which the globe spins.

Gamma Correction — Use gamma correction to control the dark to light range of the Globe display itself. This setting is useful when your work environment is darker or lighter than the average setting, such as is common in corporate "NOCs" (i.e. network operation centers that require low lighting levels).

Imagery — Use Imagery settings to control night (on/off), toggle cloud animations, or to use a quicker Intro sequence (on Globe launch).

Labels — Use Labels to toggle place name labels (check/uncheck). City labels are not shown by default. Check Show city labels if you prefer to show them. Additional labels will display on zoom.


Background — Select a background for the globe itself. Choose from among Starfield (shows a black background in a field of stars), White, Black (with no

stars), and Transparent (for combining with other charts and interpolating data).

Projection — Sets the base imagery for the globe itself. Use Projection to select between 3D Globe view and 2D Columbus (e.g. "flat earth" map projection) modes. Projection permits the user to view all of the Earth as if projected onto a flat surface as is common on two-dimensional maps.

Visuals — Check Show Sun to add our local star to the Globe visual background.

Borders — Check Show country borders or State and region to enable border display at those levels. Note that state and region borders are only applicable to one country at a time. Check any Country in the list to enable it. Check State and region for and then check the box for one or more countries to show internal political borders such as states or provinces.



CloudTest Activity Legend

In CloudTest, the Globe Legend presents CloudTest Activity, including visual cues for:

- Error Rate (Arc Color)
- Bandwidth (Arc Width)
- Response Time (Pulse Color)
- Message Rate (Pulse Speed).

The defaults shown in the CloudTest Activity Legend can be adjusted in the Activity Arcs panel (detailed below) in any custom dashboard.

Globe Filtering

The Global Activity System Dashboard, as well as the Globe widget, is fully filterable in the manner of all other SOASTA dashboards and widgets. Use the default Filter controls (shown in the breadcrumb along the dashboard top) to apply time windows, or, add more filters where necessary in custom dashboards.

The Cloud Test, Globe widget features the same transparent control panel found in its mPulse cousin. For Globe-specific settings, these controls present easy, inline control, and preclude the necessity of lower-panel settings. The legend appears in the lower left and controls are in the top-right corner.

In its default state, the Globe spins, clearly and accurately showing the current solar terminator point between night and day as well as clearly representing the twilight zone, or moving line, between the two. Click to stop the globe's rotation and use gestures to zoom. Alternately, click one of the fly-to locations on the Legend to move to it.


Cloud Provider Account Support for QingCloud

Users can now create Cloud Provider Accounts and launch Grids for the QingCloud vendor. QingCloud provides data centers in the U.S., Africa, Asia Pacific, and Europe.

Setup QingCloud as a Cloud Provider

Use the following steps to enter your valid QingCloud credentials as a CloudTest Pro Cloud Provider Account.

1. Select Central > Cloud Provider Accounts and then click New to launch the Cloud Provider Account dialog box.
2. Enter a name for the new cloud provider account. This name is used in locations and also appears in the Cloud Provider Account drop-down in the Grid Manager.
3. Change the “Type” drop-down to “QingCloud”.



4. Enter the QingCloud Access Key ID
5. Enter the Secret Access Key and then enter it in the Confirm Secret Access Key field a second time.

- Optionally, configure an access control list in the Cloud Provider Account box in CloudTest. Refer to [Cloud Provider Accounts](#) for additional Access Control List steps.

User / Tenant	Full Control	Read	Write	Use	
jgardner	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>


- Click OK to complete configuration of this Cloud Provider Account. The completed item appears in the Cloud Provider Accounts list in Central. When the Cloud Provider Account is saved, a new set of locations for QingCloud will be automatically created, if they do not already exist.

Location Name	Provider
QingCloud Asia-Pacific 1 (Hong Kong)	SOAS
QingCloud China Beijing 1	SOAS
QingCloud China Beijing 2	SOAS
QingCloud China Guangdong 1	SOAS
Rackspace Chicago	SOAS
Rackspace Dallas	SOAS
Rackspace London	SOAS
Rackspace OpenStack Chicago	SOAS

These locations must be specified during Grid Manager configuration of grids (as described below).

For more information about Locations, refer to [Using Locations](#).

Additionally, CloudTest creates all of the Server Classes supported by the QingCloud vendor.



QingCloud Server Instance Types

The following SOASTA server instance types map to the following QingCloud configurations.

SOASTA Instance Type	QingCloud Configuration
LARGE	8 GB total RAM and 2 CPU cores
EXTRA_LARGE	16 GB total RAM and 4 CPU cores
HIGH_MEMORY_EXTRA_LARGE	16 GB of RAM and 2 CPU cores
HIGH_MEMORY_DOUBLE_EXTRA_LARGE	32 GB of RAM and 4 CPU cores
HIGH_MEMORY_QUADRUPLE_EXTRA_LARGE	64 GB of RAM and 8 CPU cores
HIGH_CPU_EXTRA_LARGE	8 GB of RAM and 8 CPU cores
HIGH_CPU_DOUBLE_EXTRA_LARGE	16 GB of RAM and 8 CPU cores


These Server Instance Types can be used in either Results Server or Test Server instances.

Launching Test Servers using QingCloud

Once a QingCloud Provider Account has been created for use with CloudTest, you are ready to create a grid that will provision servers via that cloud vendor.

Creating a Grid using QingCloud


1. Select Central > Grids and then click New. The Grid Manager appears with Step 1 General displayed.




The screenshot shows the 'Grid Manager' application window with the 'General' tab selected. The window title is 'Grid Manager'. On the left, there is a sidebar with 'General' (selected), 'Server Instances', and 'Summary'. The main content area is titled 'General' and contains the following text: 'Use the Grid Wizard to manage elastic, cross-cloud computing resources, used in one or more load tests. Test Server instances will be used to generate load, and Results Service instances will be used to analyze and report on the test data in real-time.' Below this, it says: 'Enter a Grid Name, an optional Description, and a Save Location (from which the grid can be opened and managed), and then click the right arrow to go to Step 2.' The form includes: 'Grid Type:' with radio buttons for 'CloudTest' (selected) and 'mPulse'; 'Grid Name:' with a text box containing 'QingCloud: 1 Maestro and 1 RS in Every Region'; 'Description:' with an empty text box; and 'Save Location:' with a text box containing '/' and a 'Browse...' button. At the bottom right, there are 'Back' and 'Next' buttons.

2. Select the SOASTA product to which the grid pertains, which in this case is CloudTest.
3. Enter a Grid Name, and optionally, enter a description and a repository location for the new grid, and then click the right arrow.

The Step 2 Server Instances page appears.



Note: Every QingCloud server is given a bandwidth limit by the user. Total bandwidth across the given QingCloud account is capped by QingCloud. The Default cap is 1 Gbps (e.g. 8,000 Mbps). Bandwidth is specified in the CloudTest Grid Manager, Server Instances page, Provisioned Bandwidth setting.




4. Change the “Location” drop-down to one of defined QingCloud locations. For example, *QingCloud Asia-Pacific 1 (Hong Kong)* (shown in the first location above) or *QingCloud China Beijing 1* (shown in the second location above).

5. Optionally, specify additional locations such as the *QingCloud China Quangdong 1* location (or a second Beijing location that uses a different combination of results and test servers).

The screenshot shows a configuration interface for two locations. The top section is for 'QingCloud China Beijing 2' and the bottom section is for 'QingCloud China Quangdong 1'. Both sections have a 'Location' dropdown menu highlighted with a green box. The 'QingCloud China Beijing 2' section has the following settings: Cloud Provider Account: PE QingCloud Account; Test Server Instances: 1; Reserve Test Server Instances: 0 (Enter a number or percent); Provisioned Bandwidth: 1 (Mbps); Results Service Instances: One for every 50 Test Server Instances (selected); Reserve Results Service Instances: 0 (Enter a number or percent); Show advanced settings: unchecked; Total Test Server Instances: 1; Total Results Service Instances: 1. The 'QingCloud China Quangdong 1' section has the following settings: Cloud Provider Account: PE QingCloud Account; Test Server Instances: 0; Reserve Test Server Instances: 0 (Enter a number or percent); Results Service Instances: One for every 50 Test Server Instances (selected); Reserve Results Service Instances: 0 (Enter a number or percent); Total Test Server Instances: 3; Total Results Service Instances: 3.

6. Specify the number of Test Server instances, and then optionally, define Results Server Instances. For most cases, the default “One for every 50 Test Server” instances” is acceptable for result servers.
7. If you wish to combine the QingCloud servers from one location with servers from another location (or even with other cloud providers), click the Add a Location box and make the appropriate selection(s). Otherwise, click the right arrow icon to proceed.

The Step 3 Summary and Deploy Tear Down page appears. Click the “Deploy Instances” button to begin launching servers.



Note: CloudTest Pro users may see an additional Grid Monitor Database field for those configurations where more than one Results Database is available. For more about using and launching grids, refer to [Managing Grids](#).

Custom Commands for Monitoring


In prior releases Custom Commands were specific to system resources. Now, Custom Commands can be used to create Custom Monitors in supported environments except Windows. Windows support will be provided in the near future.

Custom Command monitors are entered as an inline process call (entered into the provided Monitors box, text entry field) but can also refer to an external Shell Script accessible within the given environment.

This enhancement provides the ability to monitor runtime metrics (e.g. metrics whose value is not known ahead of time).

TIP: Users should note that the output of the "script" in question must be a real number.

Custom Command monitors require an agent, SOASTA Conductor, be in use as part of command configuration. This configuration is done using the existing Monitor UI, which now includes the Custom Command field, as well as a new Enable Custom Commands for Monitoring box is found in the SOASTA Conductor field, which appears in the Conductor Capabilities section under Allow Monitoring.




Both the Allow monitoring box, and the Enable Custom Commands for Monitoring opt-in box must be checked for subsequent monitor setup to succeed.


Once the opt-in boxes in the relevant SOASTA Conductor are checked, the remaining portion of the Monitor configuration follows the same workflow found in the setup of SOASTA-provided monitors.

Creating a Custom Command Monitor

1. Create a new monitor using Central > Monitors > New.
2. In the Server Group or Monitor page, give the new monitor a name.
3. Ensure that the new monitor is associated with a Monitor Server Group setup for the host that will be monitored (shown below using the *LibertyMonitorGroup*).




Additionally, ensure that the Monitor Server Group's Connection Type has been set to the Conductor in use for the given host (e.g. as opposed to SSH).



If you're not yet familiar with CloudTest's extensive monitoring capabilities, refer to [Creating Monitor Server Groups](#) and [Creating a Monitor](#) before proceeding.


- On the System Resources page, scroll down and click Add Custom Object (the green Plus icon) and then select Custom Command from the drop-down.



- In the "Select resource type" dial that appears, select Custom Command.



- In the Add a new Monitor Server Group or Monitor, System Resources page, check the Custom Command box in the Type column.



- In the Name column, enter a name to use for the monitor. For example, *Shared DB Memory-PostgreSQL*.

TIP: Although this name is optional, it will appear on the widget title bar in any dashboard where the monitor is in display, so SOASTA recommends that

each Custom Monitor have a unique name to distinguish its purpose and the information being tracked at runtime.

8. Next, create the external shell script to use on the machine to monitor.

For example, create a shell script called `apache_shared_mem`. This script will get the sum of shared memory for apache processes on the given machine.

```
#!/bin/bash
```

```
top -b -n 1 | grep httpd | awk '{sum+=print $7} END {print sum}'
```

TIP: You can also enter your script inline in the System Resource Selection page (shown above) but SOASTA recommends doing so only for very basic scripts (e.g. usually ones that can be viewed in their entirety in the Arguments columns).

9. Change the script's permissions to make it executable. For example:

```
chmod a+x apache_shared_mem
```

10. Enter the call to the script Monitor wizard's System Resource Selection. Note that the `./` preceding the script's name is required.

System Resource Selection

Select one or more resources to monitor

Type	Name (Optional)	Sample Rate	Arguments
<input type="checkbox"/> CPU Percentage			Sec.
<input checked="" type="checkbox"/> Custom Command	Shared Memory	5	Sec. ./apache_shared_mem
<input type="checkbox"/> IO KBytes Read			Sec.
<input type="checkbox"/> IO KBytes Written			Sec.
<input type="checkbox"/> Memory Usage			Sec.
<input type="checkbox"/> Network Mbits Received			Sec.
<input type="checkbox"/> Network Mbits Sent			Sec.
<input type="checkbox"/> Per Process CPU Percentage			Sec.

Cancel Back Next

11. Complete the monitor creation.

12. At runtime, CloudTest will utilize a number returned from the given path.

13. Click Next and then complete the creation of the Custom Monitor.

The Name (Optional) value appears on the Monitor dashboard (as noted above).

Enhancements

CloudTest

Support for Transport Layer Security (TLS) 1.1 and 1.2

This release adds support for Transport Layer Security (TLS) versions 1.1 and 1.2 to the list of target-based security settings for HTTP, WSDL, and WebSocket targets.



TLS-related settings are found in the Target Editor, SSL Options section for the given target and are enabled by default in all target type for which support is provided.

Support for Server Name Indication (SNI)

This release adds support for testing sites that use the [Server Name Indication \(SNI\)](#) standard. SNI is an extension to the TLS computer networking protocol.

Java Custom Module Improvements

The Java Custom Module engine now supports JAR files built using Java 7 and earlier. In previous releases, the engine supported only Java 6 and earlier.

Metric Labeling in Monitors

Users can now assign custom names to CloudTest's out-of-the-box metrics via the System Resources Selection page of the monitor wizard.


- To label an out-of-the-box metric, check its box and type the metric label into the Name (Optional) field.

The screenshot shows the 'System Resource Selection' page of the monitor wizard. The page title is 'Add a new Monitor Server Group or Monitor'. On the left, there is a sidebar with 'System Resources' and 'Finish'. The main area is titled 'System Resource Selection' and contains the instruction 'Select one or more resources to monitor'. Below this is a table with columns: Type, Name (Optional), Sample Rate, and Arguments. The 'Per Process CPU Percentage' option is selected, and its 'Name (Optional)' field contains 'JBoss CPU'. The 'Sample Rate' is set to '5 Sec.' and the 'Arguments' field contains 'java'. At the bottom right, there are 'Cancel', 'Back', and 'Next' buttons.

Type	Name (Optional)	Sample Rate	Arguments
<input type="checkbox"/> Network Mbits Received		Sec.	
<input type="checkbox"/> Network Mbits Sent		Sec.	
<input checked="" type="checkbox"/> Per Process CPU Percentage	JBoss CPU	5 Sec.	java
<input type="checkbox"/> Per Process Memory Usage		Sec.	
<input type="checkbox"/> Per Process Thread Count		Sec.	
<input type="checkbox"/> Per Process Virtual Memory		Sec.	
<input type="checkbox"/> Performance Counter		Sec.	
<input type="checkbox"/> Process Count		Sec.	
+ Add Custom Object			

- If you are configuring a new monitor, also enter the Sample Rate and Arguments to use.


The new metric label is used in the Widget Title bar.



Updating CloudTest Lite (Non-Automated Build Upgrades)

Changes to the underlying CloudTest Lite Virtual Machine (VM) in SOASTA 54 go beyond those found in previous CloudTest Lite upgrades. Unfortunately, due to these changes, the About box upgrade process will not work, and the following manual upgrade steps are required to upgrade.

Note: This one-time, non-automated upgrade path is relatively straightforward for both Mac OS X and Windows users.



Download and Install the SOASTA 54 version of CloudTest Lite


The initial steps require the user to return to the SOASTA web site to re-initiate the free download.

1. Shut down your current CloudTest Lite virtual machine, if it is running.
2. Download the latest CloudTest Lite VMware image [here](#).
3. Unzip the file, but **do not** open the extracted VM. Note the folder where you unarchived CloudTest Lite.zip for use in the subsequent steps.

From here, follow the additional steps specific to your OS version.

Upgrade to CloudTest Lite 54 on Mac OS X

The following additional steps are performed after un-zipping the new CloudTest Lite (CTL) 54 VM. Before beginning, verify your current CTL VMs location by selecting it in VMWare's Virtual Machines Library list, and right clicking to use Show In Finder.



Note: The `Virtual Machines.localized` directory is only present if your VMs are in their default location. Omit that folder if your CTL VM is in a different location.

1. Once your CTL VM is located, open a new Terminal window on your Mac OS X desktop.
2. Change into the CloudTest Lite VM package folder:
 - For the default location, enter the following command (e.g. by substituting the values in brackets):

```
cd "/Users/[UserName]/Documents/Virtual  
Machines.localized/CloudTest Lite.vmwarevm"
```

- If your VM is in another location use:

```
cd ~/[Custom Location folder]/CloudTest\ Lite.vmwarevm/
```

3. Next, copy the data disk from the old VM to the new one.

- For example, if the default location that uses `Virtual Machines.localized` is in use, then this can be done by entering the following command in:

```
cp Virtual\ Disk\ 2* ~/Downloads/CloudTest\ Lite\ 2.vmwarevm/
```

- If both VMs are in the same folder, then the newly unarchived VM is named "CloudTest Lite 2.vmwarevm." In which case, use the following Terminal command:

```
cp -a Virtual\ Disk\ 2* ../CloudTest\ Lite\ 2.vmwarevm/
```


After completing the above steps, start the CloudTest Lite 54 VM.

Upgrade to CloudTest Lite 54 on Windows

The following additional steps are performed after installing the new CloudTest Lite 54 VM.


1. Using the file manager find the directory where the VMs live and go into the first (**old**) CloudTest Lite directory. Unless your VMWare installation folder is non-standard, this should be:

```
\Users\User\My Documents\Virtual Machines\CloudTest  
LiteOld.vmwarevm
```




2. Grab and right click on all the files that start Virtual Disk 2 and select "Copy."

TIP: Depending on your Windows setup, the file extension may not be in display.



3. Change to the CloudTest LiteNew.vmware directory.

4. Right-click in the File Manager window and then select "Paste."




After completing the above steps, restart the CloudTest Lite 54 VM.

Support for Additional HTTP Methods (78361)

In prior releases, some of the more unusual HTTP methods, including TRACE, OPTIONS, as well as methods related to HTTP Extensions for Distributed Authoring (WebDAV), went unsupported.


Now, all of the above methods are supported in both the underlying layer as well as in the SOASTA 54, CloudTest user interface, including in the Clip Editor, Message Editor, Convert Recording to Clip wizard, the Result Details widget (as well as in the Test Suite Dashboard's in situ Result Details widget).

In the Clip Editor screenshot below, an HTTP message based on OPTIONS is shown:



Name	Operation	Parameter 1
Options-msg-1	options	/
Delay1		14193 ms.
Trace Page		
HTML Document		
Trace-msg-1	trace	/

Details about the message are shown in the lower panel as in all prior releases.



Messages/Actions | Scripts | Clips | Compositions | Properties | Selected: Options-msg-1 | Results

Options-msg-1


- HTTP Request Headers
- Inputs
 - URL Values
 - Query String
- Recorded Request
 - Request Headers
 - Request Content
- HTTP Response Headers
- Recorded Response
 - Response Headers
 - Response Content
- Property Sets
- Validations
- Built in

Operation: options


URL Values: /

Query String:

Users are now able to filter these additional operations in results in the Result Details Dashboard, Operations drop-down.



As in all prior releases, details about the filtered operations are presented in the panes on the right.




Support for Monitoring JBoss 8 (30032)

Users can now monitor JBoss 8 instances using the Monitor Server Group and Monitor wizard.

Ability to put any percentile into Collection Analysis (Hierarchical) widget (84993)

A Collection Analysis (Hierarchical) widget slider now permits the user to specify a percentile rather than a Z-Value.



TouchTest


Test Suite Dashboard Improvements

This release introduces many additional improvements to the Test Suite Dashboard feature introduced as part of SOASTA 53.05, including all of the following:

- Errors Only Display in the Compositions Overview widget
- Additional Component Selection Support in Compositions Overview widget
- Import/Export of Master/Child Results in Test Suites


Errors Only Display in Compositions Overview Widget

An errors-only filter has been implemented in the Compositions Overview widget that improves the Test Suite Dashboard's usefulness for viewing test failures.



Additional Component Selection Support in Compositions Overview Widget

As noted in the Support for Additional HTTP Methods section, the Test Suite Dashboard's, Operations drop-down also offers new component selection filters.




Import/Export of Test Suite Results

As part of the Test Suite Dashboard feature, a new master/child relationship was introduced into CloudTest that didn't exist in releases prior to 53.05.

For example, if Composition A contains a clip element that launches Composition B, then when Composition A was run it had a "child" result (from Composition B). There was no facility to export this new Launch Composition (a.k.a Composition B).

Now, users can export the child composition via the Export dialog box as well as via the SOASTA Command Line utility (sCommand).

To do so via the Export box, users will check the new box, Also export any child results. Doing so will include the "child" result when you export the master result.



New `includechildresults` parameter for sCommand

For sCommand users, a new `includechildresults=true` argument can be amended to the Export command whenever used to export a result from a Test Suite composition (e.g. a master composition that includes one or more Launch Compositions) in order to include child results).

This new argument is the command line equivalent of the Export box's "Also export any child results" box (shown above). The default is false in the command-line utility, just as it is in the Export checkbox.

For example, to export result time aggregates from a Test Suite composition and all of its children, use:

```
scommand cmd=export username=bob password=secret type=result
file=myexport.csv name="/Directory/TestSuiteCompositionName/ResultNameDemo"
format=csv resultSource=resultTimeAggregates includechildresults=true
```

Launch Composition Details in sCommand JUnit/XML (88321)

For playing test compositions, Jenkins and other JUnit/XML-friendly CI tools will now include report errors/statistics for Launch Compositions. Support is also provided for text format in addition to JUnit/XML.

On the command line or in the CI tool job:

```
<path to scommand>/scommand cmd=play name="/CI Test Suites/CI iOS Trunk Mobile Tests Build Comp" file="/Users/fake/fake_directory_path" type=composition format=junitxml wait=yes failonerror=no url=http://fake:8080/concertusername=placeholder password=placeholder debug=yes
```

For CI jobs that include JUnit results this will result in enhanced statistics.

In the prior release, limited sCommand results were posted for jobs that included JUnit/XML from Test Suite compositions. In this release, additional detail for each Launch Composition within a given Test Suite composition is posted.

Test Result		
6 failures (+6)		
		292 tests (+179) Took 16 hr. add description
All Failed Tests		
Test Name	Duration	Age
CI Test Suites.build_and_install.Install IPAs Comp	15 min	1
iOS Mobile Web Tests.iFrames.Click on the iFrame Elements Comp	42 sec	1
iOS Legacy Version Tests.iOS 6.Actions.ScrollToVisible.ScrollToVisible UICatalog Dates Comp	5 min 21 sec	1
- Error Details		
Composition completed. Validation of response body did not pass. (Band "Band 1" Track "Track 1" Clip "ScrollToVisible UICatalog Dates" App Action "Day 25")		
iOS Legacy Version Tests.iOS 6.Hybrid.Paychex.Paychex Comp	51 sec	1
iOS Mobile Web Tests.Actions.Select.EverythingHasIds.Click then Tap to Select Comp	1 min 39 sec	1
iOS Mobile Web Tests.Actions.Select.EverythingHasIds.Select Actions Comp	3 min 4 sec	1

New MakeAppTouchable (MATT) Command Line Syntax

As of this release, the MakeAppTouchable (MATT) utility requires Java 7. TouchTest users upgrading to SOASTA 54 should update to this Java version. Accordingly, the syntax for running the MakeAppTouchable utility has changed in this release. Formerly, MATT syntax was:

```
java -jar MakeAppTouchable.jar -help
```

Now, under Java 7, the new syntax is:

```
sh MakeAppTouchable/bin/MakeAppTouchable -help
```

If Java 7 is unavailable at runtime, the following failure message will display:

```
MakeAppTouchable requires Java 7.
```

Bugs Fixed

CloudTest

89461: Invalid "Set-Cookie" header in response

This fix adds a new date format to the list of those parsed for cookie expiration date.

88713: View Analytics dashboard, Performance Counter widget is not showing data

The Performance Counter widget was unexpectedly blank.

88631: Problem with HTTPS recording after auto-upgrade from SOASTA 53 Conductor

Updating the Conductor resulted in this HTTPS recording issue.

88571: Conductor can't be opened on 54.01

An underlying libjpcap resulted in a broken Conductor on update.

87641: Attempting to duplicate a system dashboard and cancelling the operation does not clean up the notification on the spinner

The Spinner progress indicator would hang after an attempt to copy a System Dashboard.

87516: java.lang.NullPointerException

This null pointer error happened in a CloudTest dashboard.

87354: java.lang.UnsupportedOperationException at com.soasta.web.concerto.reporting.hb.b (hb.java:700)

This error occurred in a CloudTest dashboard when a filter passed in an empty string for an element type. Or, it passed in a list and the value field was empty string rather than null.

87232: Collection Analysis (Hierarchical) widget doesn't list the transactions

Transaction containers were not listed in the Collection Analysis (Hierarchical) widget.

86752: java.lang.NullPointer

This null pointer exception could occur while opening a monitor.

86652: First Login User Not Given Monitor Admin Rights

The initial CloudTest/TouchTest account that's created after entering your license key did not have the Monitor Administrator privilege, and therefore could not use monitoring features.

85684: Target Property Sets and Validations - Green plus used to create Property Sets and Validations disappears

The Green plus icon would inadvertently disappear from view while setting Property Sets or Validations in the Target Editor.

85634: Collection Analysis Time Filter does not update last "N Minutes" from toolbar when changed from the toolbar

This fix implements filters text updating, which results in the necessary visible update to toolbar text.

85508: Percentile label is not being updated

On the "Collection Duration Percentile" widget, changing the percentile value updates the title of the widget, but not the Y-axis label.

85247: Google Compute Engine errors are not handled gracefully while listing zones

Errors in Google Compute Engine error handling were responsible for the unexpected failure to list out GCE zones.

84998: Column resize wasn't working

Column resize didn't work as expected in the Central, Compositions list. Now, column resizing, as well as sorting, does work as expected.

84802: For input string: "below:0f64ba9a-fe47-4aa3-87dd-b795b20874be"

A non-informative, underlying error message was shown to the user. This is now handled and the exception is now shown.

84776: Uncaught RangeError: Maximum call stack size exceeded; JS line 1752

This range error from an array occurred in CloudTest Lite.

84752: GCE error handling does not catch socket timeouts

Google Compute Engine socket timeouts were not handled as expected.

84587: java.lang.NullPointerException at com.soasta.web.concerto.reporting.db.a (db.java:433)

This null pointer exception happened in a CloudTest dashboard.

84535: Global.oConcertoEditor.onBeforeSize is not a function; JS line 34

This error occurred in a Central editor.

84512: Cannot read property 'Size' of undefined; JS line 702

This JavaScript error occurred in a CloudTest dashboard

84427: java.lang.NullPointer

This null pointer exception occurred in Central.

83957: TypeError: 'undefined' is not an object (evaluating 'ErrorCaptureProxy.isResultsServiceAlive'); JS line 775

This results object error occurred in CloudTest Lite.

83823: This application is not currently available

Firefox extensions cause harmless errors that are caught anyway. Now, these are reported in a user-friendly manner.

82640: Format error converting number (externaldatasource) type: long, property name: parameter3

This DWR error occurred in CloudTest Lite.

82375: java.lang.NullPointerException

Additional null checking has been added to detect further occurrences of this error.

81946: Cannot read property '3' of null

Additional checks have been added to prevent this error.

81621: Cannot read property '2' of null

This null error occurred in Central.

81544: TypeError: this._base is undefined; JS line 220

Additional checks and a user-friendly error message has been added in the event of similar errors.

80233: <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">String

This document definition error occurred while editing a message clip.

80196: Exporting a user record that had a comma in its name split the export

An attempt to export a user's Accounting Record would result in two exported users if that user name had a comma.

80171: Remove HTML Parser (htmlparser-2.0-20060923.jar) due to CPL license issues

This fix updates the reference results after replacing HTMLParser with JTidy (due to CPL license issues).

Copyright 2014. CloudTest is a registered trademark of SOASTA, Inc. and/or its affiliates. Other names may be trademarks of their respective owners.

79848: Uncaught TypeError: undefined is not a function; JS line 2

This error occurred while loading the Composition Editor, Play tab.

**77860: NoClassDefFoundError:
com/soasta/common/command/resultsservice/CmdGetResultsServiceStatus**

A Results Service error occurred while viewing the Clip Editor.

77837: Failed to execute 'getRangeAt' on 'Selection': 0 is not a valid index

This error occurred in CloudTest Lite, Central.

67245: Attempt to delete volume already deleted should silently fail

An attempt to delete a volume that was already deleted produced this error. Now, when the volume or snapshot has been deleted from EC2 it is handled.

58458: ACL error trying to open an RSDB

An Access Control Error would occur while opening a Result Service Database from the Central list. This fix includes performance better permissions handling.

58279: PersistenceException.OwnerRequired" if a user is deleted while logged in

A fix that logs users off if they are deleted has been checked in. This applies to cases where a single user is deleted. If a user multi-selects users and then deletes them, the old error will be thrown.

49536: Grid UI Shows Server Hours when "Server Hours Tracking" is disabled

Server Hours were still posted after disablement at the license-level.

43026: ScrollToVisible scrolls to the first location correctly but not the second

This longstanding case has now been resolved alongside other scrolling issues in TouchTest.

TouchTest

89560: Recording gets stuck in pendingSelect when moving from picker to picker [[requires new TouchTestDriver](#)]

While moving directly from picker to picker, TouchTestDriver gets stuck in a `pendingSelect` in which nothing is recorded.

88662: Offline Licensing Not Working

The Licensing scenario in support of offline instances failed.

88182: Android TTW: Double click, scroll, and pan actions do not execute on Android tablets running OS 4.4.2 [[requires new TouchTest Web app](#)]

Double click, scroll, and pan actions do not execute on Android tablets running OS 4.4.2.

88059: TouchTest command descriptions are wrong

Accessor descriptions in the Action Editor (Clip Editor lower panel) were not correct.

87457: Remove the screenshot validation recording capability of Mobile Targets

This functionality has been removed from both iOS and Android versions

85900: undefined is not an object (evaluating 'editTabFrame.Global.oCompositionEditor')

This likely timing error occurred in the Composition Editor, Play tab. Additional checking code has been added for false contexts.

85129: webClick/webType does not playback [[requires new TouchTestDriver](#)]

Playback of text entered on a form (e.g., `webClick` followed by `webType`) unexpectedly.

81619: Add support for Java 1.7 in MATT [[requires new TouchTestDriver](#)]

This fix adds necessary arguments for jarsigner in `MakeAppTouchTestable` (MATT) in order to provide Java 1.7 support.

66077: Add additional Organization ID field

Partners can now customize the login screen by modifying the CSS classname, `.additionalInput`.

